


**KOWOLUX®4**  
**Compact High Intensity Weld Film Viewer**

The distinctive, red KOWOLUX viewers are to be seen in X-ray laboratories and on construction sites all over the world. They conform to European Union Low Voltage and EMC Directives 73/23/CEE and 89/336/CEE and their performance, including uniformity of luminance, is in accordance with EN 25580.

- High grade, infra-red absorbing filters
- Mains voltage lamps have an unusually long working life
- Efficient, forced air cooling protects the film emulsions
- Infinite brightness regulation gives ideal viewing conditions
- Footswitch control leaves both hands free
- Plastic, powder coating is corrosion and chemical resistant
- Interchangeable film masks have quick release fasteners



*Technical data*

Screen area, mm	205 x 85
Film density to EN 25580	3,8D
Luminance, Cd/m <sup>2</sup>	65.000
Light source	1 x 1000W
Supply required	230V AC 50Hz
Consumption, VA	1000
Dimensions (L x H x D), mm	270 x 230 x 150
Weight, kg	5,25

Catalogue No. 15.10.04

**KOWOLUX 4 / 110V Supply**  
**Catalogue No. 15.10.047**

® Registered Trade Mark of IE-NDT Ltd

- 15.10.04 KOWOLUX 4 Compact Weld  
Weld Film Viewer**  
complete with 1 x mask for  
10cm wide film
- 15.10.041 Spare Lamp, K4S**
- 15.10.042 K4/K4S – Adjustable Mask**  
Steel mask with quick fasteners  
and adjustable, rhomboid shaped  
aperture
- 15.10.043 K4/K4S – Reduction Mask,  
10 x 48cm**  
Steel mask with ledge, quick  
fasteners and rectangular  
aperture
- 15.10.044 K4/K4S – Reduction Mask,  
6 x 48cm**  
Steel mask with ledge, quick  
fasteners and rectangular  
aperture
- 15.10.045 K4/K4S– Reduction Mask,  
70mm**  
Steel mask with ledge, quick  
fasteners and rectangular  
aperture
- 15.10.048 K4/K4S – Reduction Mask,  
6 x 24cm**  
Steel mask with ledge, quick  
fasteners and rectangular  
aperture
- 15.10.046 K4/K4S – Iris Mask**  
Adjustable from 5 to 75mmØ
- 15.10.047 KOWOLUX 4 Viewer/110V**
- 15.10.0471 K4/110V – Spare Lamp**

