

KOWOLUX®4S
Compact High Intensity Weld Film Viewer

The distinctive, red KOWOLUX viewers are to be seen in X-ray laboratories and on construction sites all over the world. They conform to European Union Low Voltage and EMC Directives 73/23/CEE and 89/336/CEE and their performance, including uniformity of luminance, is in accordance with EN 25580.



- High grade, infra-red absorbing filters
 - Mains voltage lamps have an unusually long working life
 - Efficient, forced air cooling protects the film emulsions
 - Infinite brightness regulation gives ideal viewing conditions
 - Footswitch control leaves both hands free
-
- Plastic, powder coating is corrosion and chemical resistant
 - Interchangeable film masks have quick release fasteners

Technical data

Screen area, mm	205 x 85
Film density to EN 25580	4,7D
Luminance, Cd/m ²	150.000
Light source	2 x 1000W
Supply required	230V AC 50Hz
Consumption, VA	2000
Dimensions (L x H x D), mm	270 x 230 x 150
Weight, kg	5,4

Catalogue No. 15.10.14

® Registered Trade Mark of IE-NDT Ltd

- 15.10.14 KOWOLUX 4S Compact High Intensity Film Viewer**
Complete with 1 x mask for 10cm wide film
- 15.10.141 K4S – Spare Lamp**
- 15.10.42 K4/K4S – Adjustable Mask**
Steel mask with quick fasteners and adjustable, rhomboid shaped aperture
- 15.10.043 K4/K4S – Reduction Mask, 10 x 48cm**
Steel mask with ledge, quick fasteners and rectangular aperture
- 15.10.044 K4/K4S – Reduction Mask, 6 x 48cm**
Steel mask with ledge, quick fasteners and rectangular aperture
- 15.10.045 K4/K4S– Reduction Mask, 70mm**
Steel mask with ledge, quick fasteners and rectangular aperture
- 15.10.048 K4/K4S – Reduction Mask, 6 x 24cm**
Steel mask with ledge, quick fasteners and rectangular aperture
- 15.10.046 K4/K4 S – Iris Mask**
Adjustable from 5 to 75mmØ

